


# QUARTZ Diesel 3000 15W-40



## Multigrade Oil for Diesel engines

### USES

- Lubricant suited to all Diesel engines
- All operating conditions (city, road, motorway)
- Passenger cars and/or light duty vehicles before Model Year 1996
- Miscible with other lubricants

*Consult your OEM's maintenance record*

### PERFORMANCES

#### Specifications

API

CD

#### OEMS homologations

### CLIENTS BENEFITS

- Service fill viscosity stability
- Detergency and dispersivity levels adapted
- Up-to-date additivation technology, allowing a good engine operation

### CHARACTERISTICS

QUARTZ DIESEL 3000 15W-40	Units	SAE Grade 15W-40
Density at 15°C	kg/m <sup>3</sup>	887
Viscosity at 40°C	mm <sup>2</sup> /s	103
Viscosity at 100°C	mm <sup>2</sup> /s	13,80
Viscosity Index	-	135
Cleveland flash point	°C	> 200
Pour point	°C	- 24

*Mentioned values given as information*

TOTAL LUBRIFIANTS  
16, rue de la République  
92800 PUTEAUX  
1/1

QUARTZ Diesel 3000 15W-40  
August 2004  
MPC /08/04



Ce lubrifiant utilisé selon nos recommandations et pour l'application pour laquelle il est prévu ne présente pas de risque particulier.  
Une fiche de données de sécurité conforme à la législation en vigueur dans la C.E. est disponible auprès de votre conseiller commercial.