

QUARTZ 5000 DIESEL 15W-40



Multigrade oil for diesel engines

USES

- **TOTAL QUARTZ 5000 DIESEL 15W-40** is suited to all diesel engines (passenger cars and light industrial vehicles).
- **TOTAL QUARTZ 5000 DIESEL 15W-40** is suited to turbo-charged and multi-valved diesel engines.
- **TOTAL QUARTZ 5000 DIESEL 15W-40** can be used in all operating conditions (city traffic, road, motorways), whatever the season.

PERFORMANCES

| | | |
|-----------------------|---------------------|-------------------|
| Specifications | ACEA API | A2/B2 SL/CF |
| OEMs | PSA PEUGEOT CITROEN | PSA E04/D04 Niv 1 |

CUSTOMER BENEFITS

- Meets the ACEA requirements, guarantee of an high and constant quality for the lubricant.
- Multigrade oil.
- High viscosity index.
- Excellent viscosity stability .
- Excellent detergency and dispersancy.
- Very high antiwear and anticorrosion properties.
- Very good antioxidant, antitrust, antifoaming properties.

CARACTERISTICS

| TOTAL QUARTZ 5000 DIESEL 15W-40 | Units | SAE Grade 15W-40 |
|--|--------------------|----------------------------|
| Volumetric mass at 15°C | kg/m ³ | 888 |
| Viscosity at 40°C | mm ² /s | 110 |
| Viscosity at 100°C | mm ² /s | 14,3 |
| Viscosity index | - | 135 |
| Flash point Cleveland | °C | 234 |
| Pour point | °C | -30 |

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1
avril 2004

**QUARTZ 5000 DIESEL
15W-40**

Sheet updated : 01/08
Sticker reference : MPC 04/04



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant